

FOLDABLE TYPE BEST SERIES SPRING LOADED CULTIVATOR



SMSL-3-21R



SMSL-3-21R



GENERAL FEATURES

It is manufactured as 17,19,21,23,25,27,29 legs with 3-row with optional roller combination. While breaking the stubble, it cultivates the soil without turning it over. In heavy soil, it cultivates the soil up to 250 mm depth. Distance between the legs can be fixed. The legs are made of high quality spring-steel and can stretch up to 60 mm. Due to having a 70 cm working height, it can't be blocked by stalks, weeds ext. during cultivation. It can't make a tough layer under the soil and it doesn't release the soil moisture since it doesn't turn over the soil during cultivation. It stores the minerals and oxygen because it works by vibrating. It raises the crops fruitfulness Rotating harrow combination levels the soil which the cultivator cultivates by pushing. It prepares a perfect seed bed and minimizes the seed casualty.

TECHNICAL DETAILS

CODE	NUMBER OF LEG	NUMBER OF ROW	WORKING WIDTH (CM)	WORKING SPEED (KM/H)	REQUIRED POWER (HP)
SMSL-3-17	17	3	430	5.5-9	120-140
SMSL-3-19	19	3	480	5.5-9	140-160
SMSL-3-21	21	3	535	5.5-9	160-180
SMSL-3-23	23	3	585	5.5-9	180-200
SMSL-3-25	25	3	640	5.5-9	200-220
SMSL-3-27	27	3	695	5.5-9	220-240
SMSL-3-29	29	3	745	5.5-9	240-260





SOIL MASTER
AGRICULTURAL MACHINERY

HEAD OFFICE

Add: Fevzi Cakmak Mh. 10758 Sk. No: 16/G
42050 Karatay/Konya/TURKEY

T: +90 332 290 00 20
F: +90 332 290 00 19

FACTORY

Add: Büyükkayacık Osb, Yaylacık Cd. No:
23, 42250 Selcuklu/Konya/TURKEY

T: +90 332 239 18 85
T: +90 332 239 18 86
F: +90 332 239 18 87

www.soilmaster.com.tr



+90 (532) 137 01 74



info@soilmaster.com.tr



SOILMASTER AGRICULTURAL MACHINERY



For detailed information about
our products, you can scan the
QR code by your device.